


姿図



品番	DL-SD14L
光源	LED 3000K 50W
定格光束	3270.0 lm
1/2照度角	17°
ビーム角	16°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 0.29 H B 0.29 H
保守率	良 0.63
	中 0.60
	否 0.53

反射率 (%)	天井			壁			50			30			0		
	80	70	50	50	30	10	50	30	10	50	30	10	50	30	10
床	20			20			20			20			20		
室指数	照 明 率 (× 0.01)														
0.6	78	73	70	78	73	70	77	73	70	76	72	69	68		
0.8	85	79	76	84	79	76	82	78	75	81	78	75	73		
1	90	85	82	89	85	81	88	84	81	86	83	80	78		
1.25	95	90	87	94	90	86	92	88	85	90	87	84	82		
1.5	98	94	91	97	93	90	95	92	89	93	90	88	85		
2	100	100	97	100	99	96	100	97	95	97	95	93	90		
2.5	100	100	100	100	100	100	100	100	99	100	98	96	93		
3	100	100	100	100	100	100	100	100	100	100	100	99	95		
4	100	100	100	100	100	100	100	100	100	100	100	100	97		
5	100	100	100	100	100	100	100	100	100	100	100	100	99		

