


姿図



品番	DL-SD16H
光源	LED 14.5W (3500K)
定格光束	1120.0 lm
1/2照度角	20°
ビーム角	20°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 0.35 H B 0.35 H
保守率	良 0.63
	中 0.60
	否 0.53

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
床	20			20			20			20			0	
室指数	照 明 率 ( × 0.01 )													
0.6	81	77	74	81	77	74	80	76	73	79	76	73	72	
0.8	87	83	79	87	82	79	85	81	78	84	81	78	76	
1	93	88	85	92	88	84	90	87	84	89	86	83	81	
1.25	97	93	90	96	92	89	94	91	88	92	89	87	85	
1.5	100	96	93	99	95	92	97	94	91	95	92	90	87	
2	105	102	99	104	101	98	101	99	97	99	97	95	92	
2.5	109	106	104	107	105	102	104	102	100	101	100	98	95	
3	111	109	107	109	107	106	106	104	103	103	102	101	97	
4	114	112	110	112	110	109	108	107	106	105	104	103	99	
5	115	114	113	113	112	111	109	108	107	105	105	104	100	

